

# OIL WATER SEPARATORS

KCPS-1500



OIL WATER SEPARATORS

CONSTRUCTION	
Polyethylene or stainless steel tank	
Inlet Pipes - 32mm pressure UPVC CAT 17 socket	
Outlet Pipe - Water 50mm DWV UPVC V66 Socket. Oil 50mm DWV UPVC V66 Socket	
Sludge Hopper - 50mm UPVC incorporating 50mm PVC ball valve	
Tank Construction - Chemical resistant UV stabilised polyethylene thickness 5mm	
Lid Construction - Chemical resistant UV stabilised polyethylene thickness 5mm	

SPECIFICATIONS	
Model No.	KCPS-1500
Length	1500mm
Width	750mm
Height	1510mm
Nominal Volume-Litres	300
Approximate Weight - Free Standing (Excluding pump)	60kg

PART NO.	MODEL NO.	DESCRIPTION	CAPACITY	kW	VOLTAGE	PUMP
640204	KCPS-1500	KCPS-1500 Standard	1500L/H	0.37	240	KDP25-150
640078	KCPS-1500IS	KCPS-1500 Intrinsically Safe	1500L/H	0.37	415	KDP25-150
640084	KCPS-1500SS	KCPS-1500 Stainless Steel	1500L/H	0.37	240	KDP25-150



# DIMENSIONS

KCPS-1500

